



STORZ aluminio- Rosca hembra BSP



Normas: DIN 1430

Artículo	DN	R1	Distancia entre garras (D)
ALST01025D16	25	1"	31 mm
ALST0103824	38	1"1/2	51 mm
ALST01052C32	52	2"	66 mm
ALST0106540	65	2"1/2	81 mm
ALST01075B48	75	3"	89 mm
ALST01110A64	100	4"	133 mm





STORZ aluminio- Reductor




Normas: DIN 1430

Artículo	DN	Distancia entre garras (D)	Distancia entre garras (G)
ALST03052C025D	25-52	31 mm	66 mm
ALST03075B052C	52-75	66 mm	89 mm
ALST03110A075B	75-110	89 mm	133 mm





STORZ aluminio- Para manguera




Normas: DIN 1430

Artículo	DN	Distancia entre garras (D)
ALST05025D	25	31 mm
ALST05038038	38	51 mm
ALST05052C052	52	66 mm
ALST05065065	65	81 mm
ALST05075B075	75	89 mm
ALST05110A100	100	133 mm





STORZ aluminio- Rosca macho BSP



Normas: DIN 1430

Artículo	DN	R1	Distancia entre garras (D)
ALST02025D16	25	1"	31 mm
ALST0203820	38	1"1/2	51 mm
ALST02052C32	52	2"	66 mm
ALST0206540	65	2"1/2	81 mm
ALST02075B48	75	3"	89 mm
ALST02110A64	100	4"	133 mm



STORZ aluminio- Tapón



Normas: DIN 1430

Artículo	DN	Distancia entre garras (D)
ALST04025D	25	31 mm
ALST04038	38	51 mm
ALST04052C	52	66 mm
ALST04065	65	81 mm
ALST04075B	75	89 mm
ALST04110A	100	133 mm

Acoples STORZ DIN 1430

Juntas STORZ

Juntas NBR STORZ





Presión de trabajo: 16bar

Artículo	DN
NBRST025D	25
NBRST038	38
NBRST052C	52
NBRST065	65
NBRST075B	75
NBRST110A	100