

Conexiones Serie Standard

Bridas fijación SAE

Juntas para bridas SAE 3000/6000 PSI**Material:** Poliuretano**Temperatura:** Max.200°C**Presión max. de trabajo:** 350 bar

| Artículo | Ø ext | Ø int | Tamaño | Altura (mm) |
|--------------|-------|-------|--------|-------------|
| JBR08 | 25.40 | 17.02 | 1/2" | 2.79 |
| JBR12 | 31.72 | 23.36 | 3/4" | 2.79 |
| JBR16 | 39.62 | 31.24 | 1" | 2.79 |
| JBR20 | 44.45 | 36.07 | 1"1/4 | 2.79 |
| JBR24 | 53.98 | 45.34 | 1"1/2 | 2.79 |
| JBR32 | 63.50 | 54.86 | 2" | 2.79 |

| PROPERTIES | METHOD | MEASURE UNIT | SPECIFICATIONS | FOUND DATA |
|---------------------|-----------|---------------------|----------------|------------|
| Melt flow index | ISO 1133 | g/10' 220°C 3,80 Kg | 15 -40 | 20 |
| Hardeness Shore A | DIN 53505 | | 92,0 -96,0 | 95.9 |
| Tensile strength | DIN 53504 | Mpa | >=30 | 35 |
| Modulus 100% | DIN 53504 | Mpa | >=7 | 11 |
| Modulus 300% | DIN 53504 | Mpa | >=15 | 23 |
| Elongation at brake | DIN 53504 | % | >=425 | 502 |